



Tablas de selectividad: caja moldeada / apartamento modular

Selectividad entre interruptores de caja moldeada

		Aguas arriba															
		Modelo	250A		400A		630A		800A			1000A		1250A		1600A	
			S250-NE, S250-GE S250-PE, H250-NE	S400-NE, S400-GE, S400-PE	E630-NE, S630-CE, S630-GE	S800-NE	S800-RE	H800-NE, L800-NE	S1000-SE	S1000-NE	S1250-SE, S1250-NE	S1250-GE	S1600-SE	S1600-NE			
			36kA, 65kA 70kA, 85kA	50kA, 70kA, 85kA	50kA	50kA	70kA	125kA, 200kA	50kA	70kA	50kA, 70kA	100kA	50kA	100kA			
Protección de línea	TB2 S125	S125-NJ	36kA	T	T	T	T	T	T	T	T	T	T	T			
		S125-GJ	65kA	T	T	T	T	50	T	T	T	T	T	T			
	TB2 S250	S160-NJ	36kA	.	T	T	T	T	T	T	T	T	T	T			
		S160-GJ	65kA	.	T	T	T	36	T	T	50	T	T	T			
		S250-NJ	36kA	.	T	T	T	T	T	T	T	T	T	T			
		S250-GJ	65kA	.	T	T	T	36	T	T	50	T	T	T			
	TB2 S/H/L 250	H125-NJ H160-NJ	125kA	T	T	T	T	50	T	T	T	T	70	T	85		
		S250-NE	36kA	.	.	T	T	T	T	T	T	T	T	T			
		S260-GE	65kA	.	.	T	T	36	36	T	50	T	T	T			
		H250-NJ	125kA	.	.	T	T	50	T	T	T	T	70	T	85		
		S250-PE	40kA	.	.	T	T	36	36	T	50	T	70	T	T		
		H250-NE	125kA	.	.	T	T	36	36	T	50	T	70	T	85		
	TB2 E/S 630	E400-NJ	25kA	.	.	10	T	T	T	T	T	T	T	T	T		
		S400-CJ	36kA	.	.	10	25	25	25	30	30	T	T	T	T		
		S400-NJ	50kA	.	.	10	25	25	25	30	30	36	36	T	T		
		S400-NE	50kA	.	.	10	25	25	25	30	30	36	36	T	T		
		S400-GJ S400-GE S400-PJ S400-PE	70kA	.	.	10	25	25	25	30	30	36	36	T	50		
		E400-NE	36kA	T	T	T	T		
		S630-CE	50kA	36	36	T	T		
		S630-GE	70kA	36	36	T	50		
TB2 1000	S800-CJ S800-NJ S800-RJ S800-NE S800-RE	36kA	20	20			

Selectividad entre interruptor de caja moldeada e interruptor magnetotérmico

		Aguas arriba													
		S160-SJ (40kA) S160-SCJ (25kA) E160-SJ (16kA)							S250-SJ (40kA) E250-SJ (25kA) E250-SCJ (16kA)						
		In	25A	40A	63A	80A	100A	125A	160A	100A	125A	160A	200A	250A	
Protección de línea	TD3 M06, TD3 M10	6A	1000	1000	3000	3000	5000	5000	600	T	T	T	T	T	
		10A	1000	1000	2000	2000	4000	4000	5000	T	T	T	T	T	
		16A	600	600	2000	2000	3000	3000	4000	T	T	T	T	T	
		20A	600	600	2000	2000	3000	3000	4000	T	T	T	T	T	
		25A	.	600	1500	1500	2500	2500	3000	T	T	T	T	T	
		32A	.	600	1500	1500	2500	2500	3000	9000	T	T	T	T	
		40A	.	.	1500	1500	2500	2500	3000	8000	9000	T	T	T	
		50A	.	.	1500	1500	2500	2500	3000	7000	8000	9000	T	T	
		63A	.	.	.	1500	2500	2500	3000	6000	7000	8000	9000	T	

Notas: 1. Todos los ajustes de intensidad y tiempo de retardo deben ajustarse al valor máximo para el interruptor de caja moldeada aguas arriba.

2. Is expresada en kA.
3. T=Selectividad total.

Notas:

1. Valor no disponible para S160-GJ
2. Is expresada en A
3. T=Selectividad total

Cascada entre interruptor de caja moldeada e interruptor magnetotérmico

		Aguas arriba													
		S160-SJ (40kA) S160-SCJ (25kA) E160-SJ (16kA)						S250-SJ (40kA) E250-SJ (25kA) E250-SCJ (16kA)							
		In	25kA	40kA	63kA	80kA	100kA, 125kA, 160kA	25kA	40kA	63kA	100kA	125kA	160kA	160kA	100kA, 125kA, 160kA, 200kA, 250kA
Protección de línea	6A, 10A, 16A, 20A	25	25	25	25	20	40	40	40	40	30	25	20	25	
	25A	.	25	25	25	20	.	40	40	40	30	25	20	25	
	32A	.	25	25	25	20	.	40	40	40	30	25	20	25	
	40A, 50A	.	.	25	25	20	.	.	40	40	30	25	20	25	
	63A	.	.	.	25	20	.	.	.	40	30	25	20	25	

Notas:

1. Límite del nivel de defecto de cascada expresada en kA